



FEATURES

Itek AIO Barebone - 23.8" FHD, H610, 2xDDR4, M.2, 2x SSD/HDD 2.5", WiFi, BT, Pop-Up Cam, Spkr, Type-C, USB3, CR, HAS Stand

SPECIFICATIONS

Display	23.8 inch, FHD (1920 x 1080) 16:9, IPS level, Wide-Angle View, Anti-glare, LED backlight, 250 nits, 1:1000 contrast ratio, 3-Border Bezel-free, Zero Bright dot
Motherboard	ASUS® Pro H610T D4-CSM Thin Mini ITX
Chipset	Intel® H610 Chipset
CPU	Intel® Socket LGA1700 for Intel® Core™ 14th & 13th Gen Processors, Intel® Core™ 12th Gen, Pentium® Gold and Celeron® Processors* Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0** *CPU only support up to 65W *Refer to www.asus.com for CPU support list. **Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types.
Memory	2 x SO-DIMM, Max. 64GB, DDR4 3200/2933/2800/2666/2400/2133 MHz Non-ECC, Un-buffered Memory* Dual channel memory architecture Supports Intel® Extreme Memory Profile (XMP) *Actual Memory data rate support depends on the CPU types and DRAM modules, for more information refer to www.asus.com for the Memory QVL (Qualified Vendors Lists).
Graphics	1 x DisplayPort** 1 x HDMI™ port*** 1 x LVDS connector *Graphics specifications may vary between CPU types. ** Supports max. 4K@60Hz as specified in DisplayPort 1.4. *** Supports 4K@60Hz as specified in HDMI 2.1.
Storage	Total supports 1 x M.2 slot and 2 x SATA 6Gb/s ports Intel® Core™ Processors (14th & 13th & 12th Gen) - 1 x M.2 slot (Key M), type 2260/2280 (supports PCIe 4.0 x4 & SATA modes) Intel® H610 Chipset - 2 x SATA 6.0 Gb/s ports



Ethernet

1 x Realtek 1Gb Ethernet
ASUS LANGuard

Wireless

Wi-Fi AC + Bluetooth 5

Front I/O

1 X USB 3.2 Type C

*Support Quick Charging

1 x USB 3.2 Type A

1 x 3.5mm Audio Combo Jack

1 x Card Reader

Back I/O

2 x USB 3.2 Gen 2 ports

2 x USB 2.0 ports

1 x DisplayPort

1 x HDMI port

1 x Realtek 1Gb Ethernet port

2 x Audio jacks

1 x DC Power Connector (Support 19V)

2 x 3W Speakers

Speakers

Security

Kensington Lock

Cable Cover

Power

120W Adaptor

Camera

Pop-Up Camera Housing - 5Mp 2592×1944 Camera With Dual Microphone

Height Adjustable

Stand

Tool-Less Quick Release / Install Design

Elevation: 130 mm

Tilt: -15° -25°

Swivel: -30° -30°

Rotation: -90° -90°

Black Matt with Circle White Light

Cover

Thermal Kit

Approved thermal module Kit for Core I 3/5/7 CPU up to 65W TDP

VESA

Supported with ITEK custom bracket (optional)

Profile

48mm thick

Dimension

(Without Stand) 542.2 x 338.7 (H) x 54.9 (D) mm

(With Adjustable Stand) 542.2x 492.7~362.7 x 230mm

Chassis Material

ABS Carbon Fibre rear cover, Plastic stand

PACKING INFORMATION

SOCIAL MEDIA COMMUNICATION

Codice: ITPCAB2461BHW
EAN: 8056157883999

